



WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Earthborn**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Earthborn Eggshell No. 17 Paint](#)

Eggshell No.17 is a durable, washable and scuff resistant environmentally friendly paint suitable for interior woodwork. It has a silk finish and a unique formulation that is totally **oil free**, containing virtually no VOCs.

1. Coverage

Approximately 14m² per litre.

2. Colours

72 colours plus white.

3. Pack Size

750ml & 2.5L

4. Thinner (Depends on product if needed)

Water (up to 10%)

5. Uses

Earthborn Eggshell No.17 is suitable for use on interior wood – doors, window frames, furniture, shelving, skirting boards and other smooth planed wood.

N.B. Earthborn Eggshell No.17 is not recommended for floors or other heavy-duty surfaces.

6. Ingredients

Water, Binder (VAE/Soft acrylic emulsion)), Pigments (Inc. Titanium Dioxide), Fillers (China Clay, Dolomite), Preservative* (Isothiazolinone Mixture), Thickener (Methylcellulose), Dispersant (Phosphate), PH Modifier (Sodium Hydroxide).

7. Properties

Earthborn Ecopro Eggshell is totally free from oils and is virtually VOC free. It has a high solids content which gives it excellent covering properties and makes it easy to apply.

8. Preparation

For best results do not apply in temperatures below 8°C. Wood surfaces should be prepared with Earthborn Multi-Purpose Primer and lightly sanded prior to application. Previously painted surfaces should be sanded to provide a key, then primed with Earthborn Multi-Purpose Primer. Loose or flaking material must be removed. Defective wood should be repaired, exuding resin removed and knots treated with a proprietary knotting solution.

9. Instructions for Use

Stir thoroughly before use. For best results apply two coats of undiluted Eggshell No.17. Give a light sanding between coats.

10. Application

Earthborn Eggshell No.17 can be applied by brush, roller or spray gun.

11. Colouring

N/A



12. Drying Time

In normal temperatures and humidity, allow 6 - 12 hours drying time between coats. The eggshell is touch-dry after 1-2 hours. Maximum durability is achieved after 10 days.

13. Tools

Brush, roller and spray gun.

(If using a pressure pot, thin with water approx. 10-30%)

14. Cleaning

Remove as much Earthborn Eggshell No.17 as possible from tools before cleaning with warm, soapy water. To minimise water usage please avoid cleaning under running water.

15. Maintenance

Painted surfaces can be cleaned with a soft cloth or sponge and water, do not use abrasive or micro-fibre cloths. Avoid excessive rubbing as this may leave a visible mark when dry. The use of harsh detergents to remove stains is not recommended.

16. Storage & Disposal

Keep containers tightly sealed in a cool, dry and frost-free place. Unopened containers have a minimum shelf life of 12 months when stored under the recommended conditions.

Any leftover paint should not be emptied into drains or watercourses but allowed to dry and reference made to local authority disposal guidelines.

17. Safety

Please refer to Material Safety Data Sheet.

18. Water Vapour Permeability

227.5 g/m² per 24 hours.

19. Moisture Vapour Transmission

MVT value = 227.5 g/m² per 24 hours.

20. VOC Content

This product has a VOC content of less than 0.5g/L

21. Safety of Toy Standards (EN71-3:2019)

The user is recommended to test the product on the intended surface to ensure its suitability.

Our colours are made using a traditional batch process so there may be slight colour variations between batches and the colour chart. Whilst every precaution is taken to ensure colour continuity, please make sure you have sufficient paint from the same batch to complete your work.

**Synthetic preservative Contains*

Contains 1,2-benzisothiazol-3(2H)-one, Reaction mass of 5-chloro-2-methyl-1,2-thiazol-3(2H)-one and 2-methyl-1,2-thiazol-3(2H)-one(3:1). May produce an allergic reaction. Please see MSDS for more details