



WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Osmo**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Osmo Polymer Composite Maintenance Oil](#)



POLYMER COMPOSITE MAINTENANCE OIL

Ideal protection against dirt and stains!



030 Clear Satin



Product description:

Clear satin Polymer Composite Maintenance Oil penetrates the surface and will not build a film on the surface. Through the impregnation, the surface becomes water repellent as well as resistant to dirt and stains.

Recommended use:

Osmo Polymer Composite Maintenance Oil is suitable as a clear oil for maintaining and restoring weathered Wood Polymer Composites (WPC) and Bamboo Polymer Composites (BPC). Especially suitable for decking, privacy screens and garden furniture made of WPC or BPC.

Ingredients:

Based on natural plant oils (sunflower oil, soybean oil, thistle oil), paraffin, siccatives (drying agents) and water repellent additives. Dearomatized white spirit (benzene-free). VOC classification in compliance with EU regulations (2004/42/EC): out of scope. Detailed declaration of ingredients available upon request.

Technical Data:

Viscosity: 30 - 50 mPas

Odour: faint/mild, odourless after drying

Flashpoint: > 60 °C, acc. DIN EN ISO 2719

Storage:

5 years and longer if stored in the closed original can.

Surface Preparation:

The surface must be weathered, cleaned, dry and frost-free. Osmo Polymer Composite Maintenance Oil is ready to use. Do not thin. Stir well. Prior to application, the surface must be thoroughly cleaned with Osmo Polymer Composite Cleaner 8021. This en-

sure sufficient bonding. Before applying Osmo Polymer Composite Maintenance Oil, rinse thoroughly with water and allow to dry.

Methods of Application:

With Osmo Flat Brush or Osmo Decking Brush, apply very thinly and spread well. Remove excess material (pooling or streaks) with a clean dry Osmo Decking Brush. Important: the liquid oil must be absorbed into the surface. There must not be any oil remaining on the surface or in grooves. Excess oil dries very slowly and produces a glossy oil layer without sufficient adhesion to the substrate. Leave to dry for 8-10 hours. Ventilate well while drying.

Cleaning of tools:

With Osmo Brush Cleaner (free of aromatic compounds).

Drying time:

Approx. 8-10 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Ventilate well while drying. Lower temperatures and/or higher air humidity may increase drying times.

Coverage:

1 litre covers approx. 40 m² with one coat. Product coverage depends significantly on the existing surface condition. All information refers to smooth surfaces. Other surfaces may lead to deviations in coverage.

Note:

Oils enhance the natural colour of the substrate (permanent wet effect). Trial application is required! Impregnation may influence the slip resistance of the original surface. White or very light-coloured surfaces



may become slightly yellow from oiling! Non-absorbent surfaces, such as glass, glazed tiles, ceramic or plastic, must be not treated (impregnated).

Caution:

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition). Safety data sheet available on request.

Disposal:

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 12). Only completely emptied cans can be recycled.

Colour tone:
030 Clear Satin

Size:
1.0 l; 5.0 l

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 10/20