

The following Technical Datasheet is provided by Woca

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit: Woca Wood Stain Remover





# Wood Stain Remover

## Effective spot cleaner

Wood Stain Remover effectively dissolves grease, redwine, coffee, tea on unfinished, soaped, oiled or waxed interior surfaces. Wood Stain Remover is specially developed for indoor use to remove spots from wood surfaces by spraying.

- Removes stains from wood surfaces, e.g. coffee and red wine
- Ready mixed Easy to use
- Sprayable
- Contains no harsh chemicals

## Application area

May be used on unfinished, soaped, oiled or waxed interior surfaces.

# Work description

#### **Preparation**

Before using Wood Stain Remover it is advisable to make a small test at a non-visible place of the floor to insure that there will be no undesired reaction.

#### **Treatment**

Spray Wood Stain Remover evenly on the stain directly from the bottle. Leave the Wood Stain Remover to dissolve the stain for 10-20 min. Now scrub with a brush till the stain has been dissolved. Wipe down with cloth wrung in lukewarm water. Repeat operation if necessary. When the floor is completely dry apply the original surface finish, e.g. oil, wax or soap to re-establish the protection of the surface.

# Drying time

Drying time: 2-3 hours at 20°C

### Technical data

Declaration: <5% non-ionic surfactants.

Density: 1.00-1.10 g/ml.

pH-value: pH 10-11

Shelf life: 3 years

Application Temperature: +15-30°C and approx. 50% air humidity.



Colours: Colourless

Cleaning of tools: Use water

**Storage:** +10-25°C. Keep out of reach of children. Do not expose to heat (e.g.

sunlight). Store frost-free during winter and cool during summer.

Packaging: 250 ML

**Odour:** Odourless

# Maintenance and related products

WOCA Denmark A/S Tværvej 6 DK - 6640 Lunderskov +45 9958 5600 info@wocadenmark.com wocadenmark.com This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.