



# WOOD FINISHES DIRECT

The following Safety Datasheet is provided by **Blanchon**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:  
[Blanchon Wood-Ageing Agent Effects](#)

## WOOD AGEING AGENT

## SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

## SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

## 1.1. Product identifier

Product name : WOOD AGEING AGENT

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## 1.3. Details of the supplier of the safety data sheet

Registered company name : BLANCHON GROUP.

Address : 50, 8ème rue.69800.SAINT PRIEST.FRANCE.

Telephone : 00.33.4.72.89.06.06. Fax : .

fds@blanchon.com

<http://www.blanchon.com>

## 1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

## Other emergency numbers

National Poisons Information Service (Birmingham Unit) : 844 892 0111

Poisons Information Centre of Ireland (DUBLIN) : +353 1 809 25 66 or +353 1 837 9964 (medical professionals)

## SECTION 2 : HAZARDS IDENTIFICATION

## 2.1. Classification of the substance or mixture

## In compliance with EC regulation No. 1272/2008 and its amendments.

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

## 2.2. Label elements

## In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS07

Signal Word :

WARNING

Product identifiers :

EC 941-883-0

CI REACTIVE BLACK 31

613-088-00-6

1,2-BENZISOTHIAZOL-3(2H)-ONE

613-167-00-5

MIXTURE OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE ;  
2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

Additional labeling :

EUH211

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Hazard statements :

H317

May cause an allergic skin reaction.

Precautionary statements - General :

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

Precautionary statements - Prevention :

P271

Use only outdoors or in a well-ventilated area.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Disposal :

P501

Dispose of contents / container to an approved landfill.

## WOOD AGEING AGENT

**2.3. Other hazards**

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances  $\geq 0.1\%$  with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS****3.2. Mixtures****Composition :**

Identification	Classification (EC) 1272/2008	Note	%
INDEX: 022-006-00-2 CAS: 13463-67-7 EC: 236-675-5 REACH: 01-2119489379-17  TITANIUM DIOXIDE [IN POWDER FORM CONTAINING 1 % OR MORE OF PARTICLES WITH AERODYNAMIC DIAMETER $\leq 10 \mu\text{M}$ ]	GHS08 Wng Carc. 2, H351	[1] [10]	$0 \leq x \% < 2.5$
CAS: 7631-86-9 EC: 231-545-4 REACH: 01-2119379499-16  SILICON DIOXIDE		[1] [nano]	$1 \leq x \% < 2.5$
EC: 941-883-0 REACH: 01-2120068570-57  CI REACTIVE BLACK 31	GHS07 Wng Skin Sens. 1A, H317 Aquatic Chronic 3, H412		$0 \leq x \% < 1$
INDEX: 613-088-00-6 CAS: 2634-33-5 EC: 220-120-9 REACH: 01-2120761540-60  1,2-BENZISOTHIAZOL-3(2H)-ONE	GHS05, GHS07, GHS09 Dgr Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 M Acute = 1		$0 \leq x \% < 0.036$
INDEX: 613-167-00-5 CAS: 55965-84-9 REACH: 01-2120764691-48  MIXTURE OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE ; 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)	GHS06, GHS05, GHS09 Dgr Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Eye Dam. 1, H318 Acute Tox. 2, H330 Aquatic Acute 1, H400 M Acute = 100 Aquatic Chronic 1, H410 M Chronic = 100 EUH:071	B [1]	$0 \leq x \% < 0.0015$

**Specific concentration limits:**

Identification	Specific concentration limits	ATE
INDEX: 613-088-00-6 CAS: 2634-33-5 EC: 220-120-9 REACH: 01-2120761540-60  1,2-BENZISOTHIAZOL-3(2H)-ONE	Skin Sens. 1: H317 $C \geq 0.05\%$	
INDEX: 613-167-00-5 CAS: 55965-84-9 REACH: 01-2120764691-48  MIXTURE OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE ; 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)	Skin Corr. 1C: H314 $C \geq 0.6\%$ Skin Irrit. 2: H315 $0.06\% \leq C < 0.6\%$ Eye Dam. 1: H318 $C \geq 0.6\%$ Eye Irrit. 2: H319 $0.06\% \leq C < 0.6\%$ Skin Sens. 1A: H317 $C \geq 0.0015\%$	

## WOOD AGEING AGENT

**Nanoform**

Identification	Nanoform
CAS: 7631-86-9 EC: 231-545-4 REACH: 01-2119379499-16  SILICON DIOXIDE	Name of nanoform(s): SILICON DIOXIDE d50 : 2.5-50 nm Shape and aspect ratio of particles: SPHEROIDAL Crystallinity: amorphous Surface functionalisation / treatment: no

**Information on ingredients :**

(Full text of H-phrases: see section 16)

[Nano] Nanoform.

[1] Substance for which maximum workplace exposure limits are available.

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ .

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. description of first aid measures****In the event of splashes or contact with skin :**

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

**In the event of swallowing :**

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention immediately, showing the label.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

**SECTION 5 : FIREFIGHTING MEASURES**

Non-flammable.

**5.1. Extinguishing media****Suitable methods of extinction**

In the event of a fire, use :

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO<sub>2</sub>)

**Unsuitable methods of extinction**

In the event of a fire, do not use :

- water jet

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

## WOOD AGEING AGENT

**5.3. Advice for firefighters**

No data available.

**SECTION 6 : ACCIDENTAL RELEASE MEASURES****6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For non first aid worker**

Avoid any contact with the skin and eyes.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

**6.4. Reference to other sections**

No data available.

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

**Fire prevention :**

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**7.2. Conditions for safe storage, including any incompatibilities**

No data available.

**Storage**

Keep out of reach of children.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters****Occupational exposure limits :**

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
13463-67-7	10 mg/m3			A4	

- Belgium (Royal decree of 11/05/2021) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
13463-67-7	10 mg/m3				

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
13463-67-7	-	10	-	-	-	-

## WOOD AGEING AGENT

- Switzerland (Suva 2021) :

CAS	VME	VLE	Valeur plafond	Notations
13463-67-7	3 ppm			
7631-86-9	4 ppm			
55965-84-9	0.2 ppm	0.4 ppm		

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
13463-67-7	4 mg/m3				

**Derived no effect level (DNEL) or derived minimum effect level (DMEL):**

SILICON DIOXIDE (CAS: 7631-86-9)

**Final use:**

Exposure method:

Potential health effects:

DNEL :

Exposure method:

Potential health effects:

DNEL :

**Workers.**

Inhalation.

Short term local effects.

4 mg of substance/m3

Inhalation.

Long term local effects.

4 mg of substance/m3

**8.2. Exposure controls****Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

**- Hand protection**

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

**- Body protection**

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties****Physical state**

Physical state : Fluid liquid.

**Colour**

Colored

**Odour**

Odour threshold : Not stated.

low odour

## WOOD AGEING AGENT

**Melting point**

Melting point/melting range : Not specified.

**Freezing point**

Freezing point / Freezing range : Not stated.

**Boiling point or initial boiling point and boiling range**

Boiling point/boiling range : 100 °C.

**Flammability**

Flammability (solid, gas) : Not stated.

**Lower and upper explosion limit**

Explosive properties, lower explosivity limit (%) Not stated.

:

Explosive properties, upper explosivity limit (%) Not stated.

:

**Flash point**

Flash Point Interval : FP &gt; 100°C.

**Auto-ignition temperature**

Self-ignition temperature : Not specified.

**Decomposition temperature**

Decomposition point/decomposition range : Not specified.

**pH**

pH : Not stated.

Neutral.

pH (aqueous solution) : Not stated.

**Kinematic viscosity**

Viscosity : Not stated.

**Solubility**

Water solubility : Soluble.

Fat solubility : Not stated.

**Partition coefficient n-octanol/water (log value)**

Partition coefficient: n-octanol/water : Not stated.

**Vapour pressure**

Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

**Density and/or relative density**

Density : &gt; 1

**Relative vapour density**

Vapour density : Not stated.

**Particle characteristics**

The mixture contains one nanoform. See the characteristics of the particles that define the nanoform in Section 3.

**9.2. Other information**

VOC (g/l) : &lt; 10

**9.2.1. Information with regard to physical hazard classes**

No data available.

**9.2.2. Other safety characteristics**

No data available.

**SECTION 10 : STABILITY AND REACTIVITY****10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

No data available.

**10.4. Conditions to avoid**

No data available.

## WOOD AGEING AGENT

**10.5. Incompatible materials**

No data available.

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**SECTION 11 : TOXICOLOGICAL INFORMATION****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

May cause an allergic reaction by skin contact.

**11.1.1. Substances****Acute toxicity :**

CI REACTIVE BLACK 31

Oral route : LD50 > 2000 mg/kg bodyweight/day  
Species : Rat

Inhalation route (Vapours) : LC50 > 20 mg/l

SILICON DIOXIDE (CAS: 7631-86-9)

Oral route : LD50 > 5000 mg/kg bodyweight/day  
Species : Rat  
OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : LD50 > 6000 mg/kg bodyweight/day  
Species : Rabbit

Inhalation route (Dusts/mist) : LC50 >= 1000 mg/m<sup>3</sup>  
Species : Rat  
OECD Guideline 403 (Acute Inhalation Toxicity)

**Skin corrosion/skin irritation :**

SILICON DIOXIDE (CAS: 7631-86-9)

Species : Rabbit  
OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

CI REACTIVE BLACK 31

Species : Rabbit  
OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious damage to eyes/eye irritation :**

SILICON DIOXIDE (CAS: 7631-86-9)

OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Germ cell mutagenicity :**

SILICON DIOXIDE (CAS: 7631-86-9)

No mutagenic effect.

OECD Guideline 471 (Bacterial Reverse Mutation Assay)

**Reproductive toxicant :**

SILICON DIOXIDE (CAS: 7631-86-9)

Study on fertility :

Species : Rat  
OECD Guideline 414 (Prenatal Developmental Toxicity Study)

**Specific target organ systemic toxicity - repeated exposure :**

SILICON DIOXIDE (CAS: 7631-86-9)

Oral route : C = 9000 mg/kg bodyweight/day  
Species : Rat  
Duration of exposure : 90 days



## WOOD AGEING AGENT

OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Inhalation route :

C = 1 mg/litre/6h/day  
Species : Rat  
Duration of exposure : 90 days  
OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)**11.1.2. Mixture**

No toxicological data available for the mixture.

**11.2. Information on other hazards**

No other hazards known according to Regulation (EC) No 1272/2008

**SECTION 12 : ECOLOGICAL INFORMATION****12.1. Toxicity****12.1.1. Substances**

CI REACTIVE BLACK 31

Fish toxicity :

LC50 > 100 mg/l  
Species : Leuciscus idus  
Duration of exposure : 48 h  
OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity :

EC50 = 100 mg/l  
Species : Daphnia magna  
Duration of exposure : 48 h

Algae toxicity :

ECr50 >= 100 mg/l  
Duration of exposure : 96 h

SILICON DIOXIDE (CAS: 7631-86-9)

Fish toxicity :

LC50 = 10000 mg/l  
Species : Danio rerio  
Duration of exposure : 96 h  
OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity :

EC50 > 1000 mg/l  
Species : Daphnia magna  
Duration of exposure : 24 h  
OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Algae toxicity :

ECr50 > 10000 mg/l  
Species : Scenedesmus subspicatus  
Duration of exposure : 72 h  
OECD Guideline 201 (Alga, Growth Inhibition Test)**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

**12.2. Persistence and degradability****12.2.1. Substances**

SILICON DIOXIDE (CAS: 7631-86-9)

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

CI REACTIVE BLACK 31

Chemical oxygen demand :

DCO 610 g/kg

Biodegradability :

Non-rapidly degradable.

**12.3. Bioaccumulative potential**

No data available.

**WOOD AGEING AGENT**

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Endocrine disrupting properties**

No data available.

**12.7. Other adverse effects**

No data available.

**German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :**

WGK 1 : Slightly hazardous for water.

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :**

15 01 10 \* packaging containing residues of or contaminated by dangerous substances

08 01 11 \* waste paint and varnish containing organic solvents or other dangerous substances

**SECTION 14 : TRANSPORT INFORMATION**

Exempt from transport classification and labelling.

**14.1. UN number or ID number**

-

**14.2. UN proper shipping name**

-

**14.3. Transport hazard class(es)**

-

**14.4. Packing group**

-

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

-

**14.7. Maritime transport in bulk according to IMO instruments**

-

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

**Container information:**

No data available.

**Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):**

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):  
<https://echa.europa.eu/substances-restricted-under-reach>.

**WOOD AGEING AGENT****Explosives precursors :**

The mixture does not contain any substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors.

**Particular provisions :**

No data available.

**German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :**

WGK 1 : Slightly hazardous for water.

**15.2. Chemical safety assessment**

No data available.

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H351	Suspected of causing cancer .
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

**Abbreviations and acronyms :**

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

DNEL : Derived No-Effect Level

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.