

The following Technical Datasheet is provided by Craig and Rose

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

Craig And Rose Artisan Copper Patina Effect

TECHNICAL DATA SHEET

TDS ART COPPER 07/20 V2



940 -9

ARTISAN SPECIAL EFFECTS PAINTS

COPPER EFFECT & COPPER PATINA

TYPE OF MATERIAL	Artisan Copper Effect is an interior/exterior water based effect paint that can be used to create an authentic Copper or Copper Patina effect finish. The Copper effect base paint can be left as a standalone finish or the Copper Patina can be applied over the Copper to create the look of aged copper. This requires two parts for the patina effect.		
USES	An internal/external decorative effect paint that can be used on feature walls, garden ornaments and home accessories to create the look of Copper or aged patinated Copper.		
COLOURS AVAILABLE	Copper Base paint, Patinated Copper effect after patina solution.		
FINISH	Metallic or Aged Metallic	TYPE REFERENCE No.	940-9
NUMBER OF COMPONENTS	Two	MIXING RATIO	N/A
METHOD OF APPLICATION	Artisan Copper effect paint can be applied and left as a metallic Copper finish.		
	Artisan Copper Patina solution can be applied on top of the Copper effect to create the aged patina finish effect.		
	Brush the base paint onto the surface and if required then apply the patina effect solution when dry to create the effect. DO NOT ROLL or SPRAY.		
AVAILABLE PACKS	Base paint :125ml,250ml,750ml& 2.5L. Copper Patina solution : 250ml.		
SHEEN LEVEL	A Copper metallic Finish or Aged Copper patina finish.		
PRACTICAL COVERAGE PER LITRE	Base Paint approx. 8Sqm /Ltr Activator approx.		
FLASH POINT	N/A Water based.		
DRYING TIMES: SURFACE	2-4 Hours		
RECOAT	12 Hours		
ACTIVATING	After 45mins to 75 mins drying you MUST apply one or two coats of Patina solution. IF warm conditions check the drying as may need to add solution earlier. Patina effect appears after 30mins to		

THIS INFORMATION IS GIVEN IN GOOD FAITH, BUT BECAUSE OF VARIATIONS IN APPLICATION AND USE, NO WARRANTY IS GIVEN OR IMPLIED REGARDING THE RESULTS OBTAINED. USERS SHOULD SATISFY THEMSELVES OF THE SUITABILITY FOR THEIR PURPOSE AND USE.

TECHNICAL DATA SHEET

TDS ART COPPER 07/20 V2



940 -9

ARTISAN SPECIAL EFFECTS PAINTS

COPPER EFFECT & COPPER PATINA

PREPARATION	90mins. DO NOT LEAVE TO FULLY DRY BEFORE PATINA SOLUTION IS APPLIED. Practice first on a board before trying large area. Remove loose or flaking paint, fill cracks or holes with filler and sand smooth. Abrade any silk, satin or glossy surfaces before painting over. Treat any mould with scouring pad and bleach solution (1part to 3 with water).leave on surface for 15minutes then wash with clean water and dry. Surfaces must be clean and dry and
	free from grease oil or dirt or flaking coatings before painting. New dry plaster, or porous surfaces should be primed with a coat of Craig & Rose Primer Undercoat or other suitable primer.
APPLICATION INSTRUCTIONS	Stir the base thoroughly as the metal particles may settle. Do NOT thin the base paint. Apply 2 coats of the base paint with a wide brush in a criss cross motion to give a random application effect. After around 45mins to 75 mins drying you MUST apply one or two coats of Patina solution to achieve the Patina effect. If warm conditions check the drying as may need to add patina solution earlier. Patina effect appears after 30mins to 90mins. DO NOT LEAVE TO FULLY DRY BEFORE PATINA Individual results will vary due to the application method and environment. Excess may run off the surface hence use the brush to catch or re-direct any runs, also protect adjacent surfaces by masking or with polyethene to prevent damage. Allow to dry for 48hrs before exposing to rain or humidity. Artisan Copper effect base paint and Patina solution must NOT be used by children.
RESTRICTIONS ON APPLICATION AND OVERCOATING INSTRUCTIONS	The Artisan Copper patina effect is a chemical reaction and hence the amount of reaction and rust seen will vary depending on the thickness of the application and drying conditions at the time of application. Apply Patina solution at the correct time and it is recommended to practice before attempting a large area. Do not apply in temperatures near freezing as this will seriously slow down the drying and may destroy the structure of the paint.

THIS INFORMATION IS GIVEN IN GOOD FAITH, BUT BECAUSE OF VARIATIONS IN APPLICATION AND USE, NO WARRANTY IS GIVEN OR IMPLIED REGARDING THE RESULTS OBTAINED. USERS SHOULD SATISFY THEMSELVES OF THE SUITABILITY FOR THEIR PURPOSE AND USE.

TECHNICAL DATA SHEET

TDS ART COPPER 07/20 V2



940 -9

ARTISAN SPECIAL EFFECTS PAINTS

COPPER EFFECT & COPPER PATINA

	Store in a frost-free place and do not allow the paint to freeze. Do not apply to highly absorbing surfaces. Artisan Rust activator should not be applied to other types of paint.
CLEANING	Remove as much paint as possible from equipment before cleaning with water. Clean hands with warm soapy water. Do not clean the painted surface with water or detergent.
SAFETY PRECAUTIONS	COPPER PATINA SOLUTION requires special precautions during use please consult label information and follow instructions. Ensure good ventilation during application and drying. Wear Gloves and safety goggles during application. After contact with skin, wash immediately with plenty of soap and water. In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice. See can label for full safety instructions. NOT FOR USE BY CHILDREN. Safety Data Sheets are available on request.
VOC CONTENT (VOLATILE ORGANIC COMPOUNDS)	2004/42 EU Limit value for this product (Cat A/I : 200g/L) This product contains Max : 55g/L VOC.
DISPOSAL & ENVIRONMENT	Please dispose of unused paint and container responsibly. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of paint.

THIS INFORMATION IS GIVEN IN GOOD FAITH, BUT BECAUSE OF VARIATIONS IN APPLICATION AND USE, NO WARRANTY IS GIVEN OR IMPLIED REGARDING THE RESULTS OBTAINED. USERS SHOULD SATISFY THEMSELVES OF THE SUITABILITY FOR THEIR PURPOSE AND USE.