



WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Crown Trade**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Crown Trade Covermatt Drywall Primer](#)

COVERMATT DRYWALL PRIMER

A water based primer that has been developed to even out surface porosity on new dry lined walls and ceilings. It can also be used as a mist coat for new plaster where access to water is difficult. Crown Trade Drywall Primer provides the perfect base for first decoration products.

AVAILABILITY	
Colour Range	White
Packaging	10L
PROPERTIES	
Suitable Surfaces	Internal Walls and Ceilings
Drying Time @ 20°C/65%RH	Under normal drying conditions touch dry in 1-2 hours and recoat after 4 hours. Allow for adequate ventilation during the drying period
Finish	Matt
Composition	Pigment: Titanium dioxide and extenders
	Binder: Acrylic polymer
	Solvent: Water
Spreading Rate	Up to 15m ² per litre on smooth surfaces
Wet Film Thickness	67 micrometres at 15m ² per litre
Dry Film Thickness	10 micrometres at 15m ² per litre.
Volume Solids	15%
Flash Point	Not applicable
VOC Content	EU limit value for this product (cat.A/a): 30 g/l (2010). This product contains max. 1 g/l VOC.
Limitations	For interior use only. Do not apply when air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period.
PREPARATION	
New Surfaces	All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. On polished or dense surfaces use Crown Trade PX3 Primer or where a water-based alternative is required Crown Trade PX4 Primer .

TECHNICAL DATA SHEET

COATING SYSTEM	Apply one coat. Allow to dry before applying the chosen finishing coats.
APPLICATION	Stir well before and during use. Apply undiluted using good quality tools – synthetic brush, medium pile roller or spray. For airless spray, dilution should not be required. For further information follow the spray manufacturer's guidelines.
CLEANING	Return surplus material to container. Wash tools & equipment with clean water or a warm soapy solution & rinse immediately after use.
STORAGE	Store upright and secure. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not store below 5°C or above 40°C.
HEALTH AND SAFETY	Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Crown Trade Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Crown Paints products are freely available from the place of purchase or the address below. Do not empty into drains, watercourses or access routes to septic tanks.
GENERAL INFORMATION	<p>Apply all products in accordance with BS 6150: Code of practice for painting of buildings and BS 8000: Part 12: Code of practice for decorative wallcoverings and painting.</p> <p>Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Crown Paints is unable to guarantee results as it has no control over the conditions under which its products are applied.</p> <p>Before using this product please ensure you have the latest information. For help or more information contact the Crown Trade Customer Relations Team on:</p> <p>Tel: 0330 0240297</p> <p>Fax: 0330 0240278</p> <p>e-mail: info@crowntrade.co.uk</p> <p>website: www.crowntrade.co.uk</p> <p>This information is correct at date of issue January 2021</p>