



WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Dulux Trade**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Dulux Trade Stain Block Matt](#)

STAIN BLOCK MATT

Dulux Trade Stain Block Matt is a water-based primer/ topcoat suitable for use on interior walls and ceilings. It is formulated to prevent the migration of stains through the finished paint film and to seal and bind dry, friable and powdery interior surfaces such as plaster, brick and distemper. It is the effective treatment for stains caused by: water-based and solvent-based inks, crayon, biro, coffee, grease, scuff marks, water and nicotine.

KEY BENEFITS

- Interior Walls & Ceilings
- For Stains Including Smoke Damage, Nicotine & Inks
- Seals Powdery Surfaces, Limewash & Distemper

PRODUCT INFORMATION

Typical Use

Suitable for use on normal interior wall and ceiling surfaces.

Pack Size

1L, 2.5L and 5L.

Colour Range

White only.

Composition (nominal)

Pigment: Titanium dioxide, zinc oxide & inert extenders.

Binder: Water-based emulsion.

Solvent: Water.

Volume Solids

43% (nominal).

SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry) and free from all defective or poorly adhering material such as efflorescence, dirt, grease or wax.

Where necessary, surfaces should be rubbed down using a suitable abrasive paper and then dusted off. Do not abrade **Dulux Trade Stain Block Matt** before recoating.

Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE.

After suitable surface application, apply 1 coat of **Dulux Trade Stain Block Matt** to all bare or

STAIN BLOCK MATT

stained surfaces and allow to dry. Two coats will be necessary for difficult stains.

When blocking stains caused by water or damp, make sure the original cause of the problem has been rectified. When **Dulux Trade** Stain Block Matt is applied initially, it will draw the stain into itself and then seal it – this is not a defect.

Finish with another 1-2 coats of **Dulux Trade** Stain Block Matt or finish with the appropriate **Dulux Trade** paint system.

APPLICATION METHOD

Brush or short pile roller only. Do not spray.

As with all water-based paints, do not apply at temperatures below 8°C (as recommended by British Standard BS 6150).

Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 14m² per litre.

Thinning

This product does not require thinning.

Spray Recommendations

This product is not suitable for spraying.

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

Always read full Health, Safety & Environmental Information on can before use.

Drying Times

Single coat at standard thickness:

Touch Dry: Dependent on temperature and humidity.

Recoat: 6-8 hours. *Note:* on very porous surfaces, a longer drying time may be required.

Cleaning Up

After use, remove as much product as possible from equipment before cleaning with water.

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at duluxtrade.co.uk/sustainability.

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat.: A/h): 30g/l (2010). This product contains max. 0.05g/l VOC. VOC content: Trace (<0.1%).



Issued 08/23

307

STAIN BLOCK MATT

Safety datasheet is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting duluxtrade.co.uk.

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, and Community RePaint are trademarks of the AkzoNobel group. © AkzoNobel 2023.