



# WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Ronseal**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:  
[Ronseal 6 Year Anti-Mould Paint](#)

# PRODUCT DATA SHEET

## RONSEAL 6 YEAR ANTI-MOULD PAINT

Ronseal Anti-Mould Paint is protected for up to 6 years from surface mould growth. Ronseal Anti-Mould Paint is quick drying, easy to wipe clean and is moisture and steam resistant.

### INTRODUCTION

Ronseal 6 Year Anti-Mould Paint contains state of the art, encapsulated biocide technology.

Ronseal 6 Year Anti-Mould Paint's advanced formula is specifically designed to be used in areas of high humidity and condensation where mould can rapidly develop.

Ronseal 6 Year Anti-Mould Paint is protected from all common forms of mould (including black mould) preventing build up on the paint surface providing long lasting protection against the damaging effects of mould growth.

Ronseal 6 Year Anti-Mould Paint is easy to apply, with an easy to wipe clean, durable finish.

### COMPOSITION

Ronseal 6 Year Anti-Mould Paint is a low odour, water based, system containing encapsulated biocide technology.

### PROPERTIES

Appearance – White / Off-White Liquid.  
VOC Content – Low (0.3-7.99%).  
Odour – Low, inoffensive.  
Solubility – Miscible with water.  
Flash Point (°C) – >60 CC

### FIELDS OF APPLICATION

Ronseal 6 Year Anti-Mould Paint can be used in damp and moisture prone conditions such as kitchens and bathrooms. Usage within exceptionally damp or moisture prone areas will result in reduced performance.

### APPLICATION PROCEDURE

#### PREPARATION

Ensure all sources of damp, including structural, plumbing faults and rising damp, are repaired prior to treatment.

Surfaces should be clean, free from dust and loose material.

Ensure the surface is completely dry.

If mould is present treat with a proprietary fungicidal wash, following the manufacturer's instructions.

Repair any holes, cracks and surface imperfections using the appropriate Ronseal Smooth Finish Filler remembering to sand down any rough areas.

Allow any new plaster to dry for 7 days prior to application.

### APPLICATION

Stir well before use. If using to seal bare surfaces, thin the paint by 10% with clean water. Apply 2 coats using a brush or roller. When covering strong colours more coats may be required. Allow 4 hours between coats. Allow a minimum of 24 hours for the paint to fully dry before subjecting the room to condensation.

### COVERAGE

13m<sup>2</sup> per litre depending on the texture and porosity of the surface being treated.

### DRYING TIME

Touch dry in 1-2 hours. Allow 4 hours between coats.

Low temperatures, poor ventilation or high humidity will significantly extend drying times.

### CLEANING OF TOOLS

All equipment should be cleaned immediately after use with clean water and detergent.

Remove as much product as possible from equipment before washing.

### MAINTENANCE

Redecorate as required.

### IMPORTANT NOTES

Always read the instructions carefully before use.

Do not apply if surface or air temperatures are below 10°C.

Allow new plaster to dry for at least 7 days prior to application of Ronseal 6 Year Anti-Mould Paint

### STORAGE

Store in a cool, well ventilated place away from heat and sources of ignition. Store upright and carefully reseal partly used containers.

To avoid risk of spillage, always store and transport in a secure and upright position.

### HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Safety data sheet available on request.

### FLAMMABILITY

Flash point >60°C.

Non-Flammable.

### SUPPLY

Available from DIY outlets.

### SIZES

250ml and 2.5 litre resealable containers.

### DISPOSAL

Some local authorities have special facilities for the disposal of waste coatings.

Do not empty product into drains or watercourses.

### LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control. Standard codes of painting practice should be followed.

## **INFORMATION AND SERVICE**

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

### **DATA SHEETS**

Data sheets on other Ronseal products are available on request from our Technical Services Department.

Sherwin-Williams Diversified Brands Ltd operates a quality management system that complies with the requirements of ISO 9000:2008 (Certificate No. FM 01669).

Sherwin-Williams Diversified Brands Ltd operates an Environmental Management System that complies with the requirements of ISO 14001:2004 (Certificate No. EMS 35924).

**Sherwin-Williams  
Diversified Brands Ltd  
Thornccliffe Park  
Chapelton  
Sheffield  
S35 2YP**

Tel: +44(0)114 246 7171  
Fax: +44(0)114 245 5629

*Registered in England 2968830*

E. Mail: [enquiry@ronseal.co.uk](mailto:enquiry@ronseal.co.uk)  
Website: [www.ronseal.co.uk](http://www.ronseal.co.uk)

Ronseal is a Registered Trademark of the Sherwin-Williams Company.