



# WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Ronseal**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:  
[Ronseal Anti Condensation Paint](#)

# PRODUCT DATA SHEET

## RONSEAL ANTI CONDENSATION PAINT

**Ronseal Anti Condensation Paint is an insulating, durable paint designed to permanently reduce condensation on interior walls and ceilings. It can be used either as a top coat or can be overcoated with coloured emulsion. Ronseal Anti Condensation Paint is supplied in a matt white finish.**

### INTRODUCTION

Ronseal Anti Condensation Paint is a water based coating that will permanently reduce the formation of condensation on interior walls and ceilings. The paint is insulating and thus prevents the formation of condensation. It dries to a tough, scrubbable, moisture resistant surface but it can also be used as an insulating basecoat for emulsion paint if an alternative colour is desired.

Ronseal Anti Condensation Paint is low odour and quick drying and is supplied in a matt white finish.

### COMPOSITION

A water based paint containing an acrylic copolymer, fillers and insulating additives.

### PROPERTIES

Appearance – white liquid.  
Odour - Characteristic.  
Solubility – Miscible with water.  
VOC content – max 18 g/l (Low)

### FIELDS OF APPLICATION

Suitable for use on all interior walls and ceilings.

### PREPARATION

Remove any wallpaper, loose paint or plaster should also be removed by sanding the surface lightly. Take care when sanding, always wear a face mask designed to avoid the inhalation of dust.

Ensure the surface is clean and dry. Any mould should be removed with Ronseal 3-in-1 Mould Killer\* and damp stains should be covered with Ronseal One Coat Damp Seal.

\*Use biocides safely. Always read the label and product information before use.

### APPLICATION

Ensure temperature is 10°C or above. Ensure the area is well ventilated during application and drying.

Stir the paint thoroughly prior to and during application. Using a brush or roller apply two generous coats, allowing 4 hours between coats.

If using as a basecoat allow 4 hours after the application of the 2<sup>nd</sup> coat before over painting.

### COVERAGE

One litre will cover up to 6 square metres with one coat.

### CLEAN UP

Wash brushes whilst still wet in warm soapy water.

Remove as much product as possible from brushes prior to cleaning. Do not empty any unused coating into drains or water courses.

Some local authorities may have special facilities for the disposal of waste coatings.

### HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Safety Data Sheet available on request.

### FLAMMABILITY

Not flammable.

### SIZES

Available in 750 ml, 1 litre & 2.5 litre re-sealable containers.

### LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control.

### INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require on +44(0)114 240 9469.

Sherwin-Williams Diversified Brands Ltd operates a quality management system that complies with the requirements of ISO 9000:2008 (Certificate No. FM 01669).

Sherwin-Williams Diversified Brands Ltd operates an Environmental Management System that complies with the requirements of ISO 14001:2004 (Certificate No. EMS 35924).

**Sherwin-Williams  
Diversified Brands Ltd  
Thornccliffe Park  
Chapelton  
Sheffield  
S35 2YP**

Tel: +44(0)114 246 7171  
Fax: +44(0)114 245 5629

Registered in England 2968830

E. Mail: [enquiry@ronseal.co.uk](mailto:enquiry@ronseal.co.uk)  
Website: [www.ronseal.co.uk](http://www.ronseal.co.uk)

Ronseal is a Registered Trademark of the Sherwin-Williams Company.

Issue 1. October 2015